

Application Note

>> ANw3.5: Answering an incoming call

TARGET	B40h-09gg + eDsoft-w302 v1.0
NEED	When an incoming call is received, the Wavecom product informs the attached equipment of the call. The attached equipment then decides if the call should be accepted.
DESCRIPTION	<p>When receiving an incoming call it is possible for the attached equipment to either accept the call, to let the Wavecom product answer the call automatically, or to not answer the call and then to let the Wavecom product automatically call a pre-defined number using the 'call-back mechanism'.</p> <p>This application note describes how the attached equipment can instruct the Wavecom product to answer an incoming call.</p>

CONFIGURATION

Wismo configuration	<ul style="list-style-type: none"> - The value of the <code>PPPMODE</code> parameter will determine the communication type: IP modem, transparent modem, ... - <code>ANSWERMODE</code> must be configured in accordance with the ATSO configuration for not interacting. - <code>RINGCOUNT</code> must be configured for the number of rings before answering the call. - The <code>CALLSCREENNUM</code> parameter configuration with a decimal phone number need the caller line identity service from the operator and the <code>AT+CLIP=1</code> command sent to the Wavecom software
Automatic answer deactivation	When the <code>ANSWERMODE</code> parameter is set to 0, the Wavecom product lets the attached host decide whether the incoming call should be accepted or ignored.
AT#	<code>ANSWERMODE=0</code>

OPERATION

Ring information	<p>When receiving an incoming call, the Wavecom product informs the attached equipment via the serial port. The Wavecom product issues a '+CRING:xxx' message on the serial port for each ring signal received on the GSM line.</p> <pre>+CRING</pre>
Caller ID information	<p>If the attached network subscription includes a caller ID service, the CLI (Calling Line Identity) is understood by the Wavecom software.</p> <p>Depending on the telecom carrier, this service may be optional at an additional charge to the subscriber.</p> <pre>+CLIP:"xxxxxxxxxxxx", ...</pre>
Accepting the call	<p>To direct the Wavecom product to accept this call, the attached equipment must send the 'AT#ACCEPT' command via the serial port.</p> <p>The Wavecom product then goes off hook and attempts to establish the connection as specified in the <code>PPPMODE</code> parameter (PPP client, server or transparent modem).</p>
AT# command	<code>AT#ACCEPT</code>
Ignoring the call	If the attached equipment decides that the incoming call should not be answered, it should not send the 'AT#ACCEPT' command via the serial port, the Wavecom product will therefore ignore the call.

>> ANw3.5: Answering an incoming call

LINKS

AT# PARAMETERS	PPPMODE
AT# COMMANDS	CONNECTIONSTART
APP. NOTES	ANPPP_Server (ANw3.2) - ANAutomatic_Answer (ANw3.4) - ANAutomatic_Callback (ANw3.3)

PROCESS DIAGRAM

